

Krantyp:	Ausladung: (mtr.)	Hakenhöhe: (mtr.)	Schwenkradius: (mtr.)	Tragkraft min./max.: (kg)
<u>13K</u>	18	18	2,25	750/1220
<u>20K</u>	24	20	2,75	850/2000
<u>26K</u>	26	20	2,30	1000/2500
<u>27K</u>	28	20	2,80	850/3000
<u>27K</u>	28	20	2,80	1000/3000
<u>28K</u>	28	20	3,00	1000/2500
<u>28K</u>	30	22,5	2,50	800/3000
<u>32K</u>	30	22	2,50	1000/3500
<u>33K</u>	30	20	2,80	1000/3000
<u>35K</u>	33	20	3,00	925/3500
<u>35K</u>	36	20	2,50	725/4000
<u>42K</u>	36	20	2,50	1100/4000
<u>42K.1</u>	36	21	2,50	1100/4000
<u>50K</u>	40	23,1	3,50	950/4500
<u>63K</u>	43	23,1	3,60	1100/6000
<u>20SE</u>	24	19,1	1,90	850/2000
<u>22SE</u>	25	19,1	1,90	900/2000
<u>28SE</u>	28	21	1,90	1000/2500
<u>KSD 4310</u>	43	28	2,30	1050/5000
<u>KSD 4515</u>	48	28	2,50	1200/6000
<u>Terex CBR 40H</u>	40	25,6	2,70	1000/4000
<u>Terex CBR 32Plus</u>	32	21,6	2,30	1000/4000
<u>FB Gru GX251</u>	24,3	9,8 - 23,8	1,7	1000/4000
<u>Potain HD21A</u>	25	18,5	2,30	800/2000
<u>Potain HD26A</u>	28	21	2,20	800/3000
<u>Potain 321C</u>	25	20	2,35	1000/2000
<u>Potain 326D</u>	30	20	2,50	1000/3000
<u>BT13</u>	21	17,2	2,38	600/1800
			Außenkante Standfläche	
<u>Gelco G2626</u>	25,5	16,90 - 29,50	3,60 x 3,60m	700/1500